

Siphonic urinal rimless

84028.1



TECHNICAL DATA

Order no.	84028.1
Certified to	EN 80, EN 13407
matching for	LIS CU2 Concealed frame for urinal without integrated control, order no. 89266.4
Specification	rimless 1-l flushing siphonic urinal Only to be used with cover Only in combination with fixing set, order no. 89280.8
Water inlet	concealed, 2-6 bar
Outlet	horizontal
Flushing	1 l
Flushing rate	minimum 0.3 l/s - 0.6 l/s
Weight	13,5 kg
Accessories excl.	Urinal cover, order no. 89428.2
Mounting acc. incl.	Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	LIS CU2 horizontal inlet connection, order no. 89009.7 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), order no. 89418.1 1-litre siphon with horizontal outlet DN 40 (standard CH), order no. 89418.2 2-litre siphon with horizontal outlet DN 40 (standard UK), order no. 89418.3

Mounting acc. excl.	Stone screw fixing set M12 Changing set LAUFEN Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal rimless Laufen-VAL, sanitary ceramic
EN 80, EN 13407
dimensions 305 x 365 x 560 mm (with cover 905 mm)
only to be used with cover
1-l flush, water inlet concealed, outlet horizontal,
flushing rate minimum 0.3 l/s - 0.6 l/s
Special feature: Surface refinement LCC (only white), rimless, vacuum and performance tested
Further options / accessories: LIS CU2 horizontal inlet connection, 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), 1-litre siphon with horizontal outlet DN 40 (standard CH), 2-litre siphon with horizontal outlet DN 40 (standard UK), urinal cover, LIS CU2 concealed frame for urinal without integrated control
Order no. 84028.1

TECHNICAL DRAWINGS / S 1 : 20

