

**Siphonic urinal rimless
84028.6**



TECHNICAL DATA

Order no.	84028.6
Certified to	EN 80, EN 13407, EN 15091
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5
Specification	Rimless 1-l flushing siphonic urinal Electronic control with Bluetooth for 230 V / 6 V pre-assembled Only in combination with fixing set, order no. 89280.8
Water inlet	concealed, 2-6 bar
Outlet	horizontal
Flushing	minimum 0.5 l/s - 3.0 l/s
Flushing rate	minimum 0.3 l/s - 0.6 l/s
Weight	13,5 kg
Mounting acc. incl.	Electronic control 230 V Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	All siphons has to be used in combination with the outlet connection pipe (order no. 89497.3) 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), order no. 89418.1

Mounting acc. excl.	Stone screw fixing set M12 Changing set LAUFEN Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal rimless Laufen-VAL, sanitary ceramic electronic controlled with Bluetooth
EN 80, EN 13407, EN 15091
dimensions 305 x 365 x 560 mm
minimum 0.5 l - 3.0 l flush, water inlet concealed, outlet horizontal, flushing rate minimum 0.3 l/s - 0.6 l/s
electronic control 230 V / 6 V
Special feature: Surface refinement LCC (only white), rimless, vacuum and performance tested
Further options / accessories: 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), LIS CU3 concealed frame for urinal with integrated control
Order no. 84028.6

TECHNICAL DRAWINGS / S 1 : 20

